Daily Wash Checklist For Site Personnel

Doto	Store Leastion	Store #
_	Store Location:	_ Store #
Comp	leted by:	-
Check		
Off		
Mecha	inical Room	
	Verify room heater working during cold weather	
-	Verify high pressure pump oil level is visible in sight gauge	
	Verify air compressor pressure is above 90 psi	
	Check for water, oil or chemical leaks. Listen for air leaks	
-	Drain water from air compressor tank & all separator bowls	
	Check chemical levels. Fill & re-order as needed	
	Check chemical lines for air bubbles, there should be solid che	mical from tank to pump
		· ·
Tunne	l Walk-Thru	
	Push Emergency Stop Button (E-Stop) to disable car wash	
	Verify tunnel heaters working during cold weather	
	Check conveyor for foreign objects or ice build-up especially a	t entrance and exit ends
	Check for air, chemical, water leaks	
	Check all cleaning material for foreign objects or excess wear	
	Check blower intake screens for foreign objects	
-	Check conveyor trench for water build up	
	Remove any foreign objects from floor. Hose down tunnel wal	ls and floor.
	Pull Emergency Stop Button to re-enable the car wash	
	Check for two Signal Lights on Photo Eye	
Run To	est Car	
	ure a customer or employee remains in the driver's seat)	
	Program a best wash and run wash	
	Verify all foamers and nozzles spray correctly	

Program a best wash and run wash
Verify all foamers and nozzles spray correctly
Verify proper equipment sequence and operation
Check all wash components for proper operation and timing
Listen for abnormal noises
Verify exit traffic light & wind curtain operation (cold weather sites)
Check cleanliness & dryness of vehicle

Note: Wind curtains should be open for summer operation.

Note any problems below. Advise site manager. Call service provider if needed.